



CT LUCIA 611P
CT LUCIA 611PY
Technical Specifications
(EU Version)



CT LUCIA 611P

CT LUCIA 611PY



CT LUCIA® 611P – fully preloaded

Optic Design	Monofocal, aspheric (aberration correcting)
Material	Hydrophobic acrylic with heparin coated surface
Optic Diameter	6.0 mm
Total Diameter	13.0 mm
Haptic	Step vaulted
Lens Design	Single-piece
Incision Size	2.2 – 2.6 mm (depending on diopter)
Company Labeled A-Constant ¹	119.9
Diopter Range	From +4.0 to +34.0 D, 0.5 D increments
ACD	6.14
Abbe number	51
Implantation in	Capsular bag



CT LUCIA 611PY – fully preloaded

Optic Design	Monofocal, aspheric (aberration correcting)
Material	Hydrophobic acrylic with heparin coated surface and blue light filter
Optic Diameter	6.0 mm
Total Diameter	13.0 mm
Haptic	Step vaulted
Lens Design	Single-piece
Incision Size	2.2 – 2.6 mm (depending on diopter)
Company Labeled A-Constant ¹	119.9
Diopter Range	From +4.0 to +34.0 D, 0.5 D increments
ACD	6.14
Abbe number	50
Implantation in	Capsular bag
Injector / Cartridge Set (relevant for CT LUCIA® 611P and CT LUCIA® 611PY)	<p>BLUEJECT™ 2.0 Injector for diopter range +4.0 to +24.0 D</p> <p>BLUEJECT 2.2 Injector for diopter range +24.5 to +30.0 D</p> <p>BLUEJECT 2.4 Injector for diopter range +30.5 to +34.0 D</p>

¹ Please refer to www.meditec.zeiss.com web pages for optimized A-Constants.



0297

CT LUCIA 611P / 611PY



Carl Zeiss Meditec AG

Goeschwitzer Str. 51–52

07745 Jena

Germany

www.zeiss.com/ct-lucia

www.zeiss.com/med/contacts



EN_32_022_00521

The contents of the brochure may differ from the current status of approval of the product in your country. Please contact our regional representative for more information. Subject to change in design and scope of delivery and as a result of ongoing technical development. CT LUCIA is a registered trademark of Carl Zeiss Meditec. Printed on elemental chlorine-free bleached paper. © 2016 by Carl Zeiss Meditec AG. All copyrights reserved.